

ENVIROGREEN AUSTRALIA

A NATURAL BUSINESS



Shed 2, 23 North Creek Road, Ballina 2478

P: 02 6681 1532 M: 0410 511 645 E: info@envirogreenaustralia.com.au W: www.envirogreenaustralia.com.au

RAPID FIRE

SPRAY AND FOAM DISPENSER

RAPID FIRE uses just one control knob for water and chemical selection preventing mixing of chemicals and ensuring accurate dilutions. The unique design also allows complete water flow through the system for full force rinse and 100% ON/OFF product selection ensures accurate dilutions with full water and chemical flow. RAPID FIRE is ideal for cleaning and sanitising grocery store meat rooms, seafood and meat departments, kitchen and food preparation areas, food processing and packaging plants and school and school and health club locker rooms and showers plus anywhere large surface cleaning, sanitising or disinfecting is needed.

- Single control knob virtually eliminates improper use or dilutions and rotates 360° to eliminate potential damage
- Stainless steel design holds up in the most extreme environments
- Internal components made from chemical-resistant polypropylene
- Built in foam wand hanger helps prevent loss or damage
- Optional hose hanger has innovative "stain relief" feature that eliminated dispenser damage
- Multiple accessories include hoses, foam wands, spray guns and nozzles to fit almost any need
- Unique flow path for full power 6gpm (23lpm) rinse flow
- Easily replaceable chemical injector for fast service and choice of different flow rates - 2.7gpm (10.2 lpm) standard
- Brass outlet threads eliminates leaks from cross threading




MODEL NUMBERS AND KITS

6300-1	Dispenser only
6300-2	Dispenser with 44-3RG red outlet hose, 44-3-6 black inlet hose, and 40-14QD spray gun / foam wand
6300-3	Dispenser with 44-3RG red outlet hose, 44-3-6 black inlet hose, 28-1QD spray gun and 2902GQD foam wand
6300-4	Dispenser with 44-3RG red outlet hose, 44-3-6 black inlet hose, 40-14QD/292QD spray gun / foam wand and 44-89-112 backflow preventer
6300-5	Dispenser with 44-3RG red outlet hose, 44-3-6 black inlet hose, 28-1QD spray gun, 292GQD foam wand and 44-89-112 backflow preventer

SPECIFICATIONS

Measures 203mm W x 236mm H x 137mm D
10 L injector flow rate
Operating range 20-125 psi
Water temperature up to 71°C
Functions with up to 15 meters of 13mm ID hose



SMART. SAFE. GREEN
A NEW WAY TO CLEAN

